SMART TRADING ASIA (PVT) LTD

Lot No. 3, Maithree Mawatha, Industrial Estate, Ekala, Ja-Ela, Sri Lanka.
Tele: 011 4 324 280 | 011 4 324 281 | Hotline: 077 0 034 200-4 | Fax: 011 2 225 835
E-mail: smarttradingasia@gmail.com

HOT MELT DOUBLE SIDED TISSUE TAPE



DA9005W D/S Tissue Tape adopts non-woven tissue as carrier, coated with Synthetic Rubber resin adhesive on both sides, and protected with 95gsm white double-sided silicone release paper.

DA9005W D/S Tissue Tape is suitable for general bonding, bag sealing, photos sticking, envelop sealing, light shopping bag making etc.

TYPICAL PHYSICAL PROPERTIES

PROPERTIES	METRIC	ENGLISH	TEST METHOD
Total Thickness	90 Micron	3.6 Mil	PSTC-133 / ASTM D 3652
Adhesion to Steel	15 N/25mm	54.0 Oz./In.	PSTC-101 / ASTM D 3330
Tack Rolling Ball	20 cm	8.0 In.	PSTC-6 / ASTM D 3121
Tensile Strength	40 N/25mm	3.5 Lb/In	PSTC-131 / ASTM D 3759
Elongation	3.5 %	3.5 %	PSTC-131 / ASTM D 3759
Service Temperature	-10 ~ +60 °C	+14 ~ +140 °F	———
Applying Temperature	+10 ~ 40 °C	+50 ~ +105 °F	———

PRODUCT FORM & AVAILABLE SIZE

Roll Width 5mm,10mm,12mm,24mm,30mm,48mm,72mm,500mm,1020mm

Log Roll: 1020mm, 1240mm x 45M / 50M

IMPORTANT NOTE

1. The data above are typical values only, and should not be used for specifications purpose.
2. Tolerance: Thickness: ±10%; Width: ±3mm; Length: Cut Roll: ±0.3m, Jumbo Roll ±0.5%.

STORAGE & SHELF LIFE:

12 months when stored at 21°C (70°F) / 50% relative humidity out of direct sunlight.

SUGGESTIONS FOR PRODUCT APPLICATION:

It is essential that the user evaluate the product to determine whether it is fit for a particular purpose and user's method of application. Good results will be obtained when applied to a clean, dry surface with a suitable pressure on products between +10 ~ +40°C (+50 ~ +105 °F).