SMART TRADING ASIA (PVT) LTD

Lot No. 3, Maithree Mawatha, Industrial Estate, Ekala, Ja-Ela, Sri Lanka.
Tele: 011 4 324 280 | 011 4 324 281 | Hotline: 077 0 034 200-4 | Fax: 011 2 225 835
E-mail: smarttradingasia@gmail.com

Technical Data Sheet

DOUBLE-SIDED EVA FOAM TAPE



EVA Foam Tape is made of Ethylene-vinyl acetate Foam coated with Hot melt Adhesive

- **Color:** Black
- **Thickness (mm):** 1
- **Length:** 10m | 5m | Custom length
- **Width:** Custom width

APPLICATIONS

- Applicable for permanent fixing.
- For irregular surfaces.
- For mounting decorative.
- Objects in cars machines or houses.
- Anti-shock interlayer in machines.
- Mounting decorative objects in cars, nameplates, signs, small die-cast parts, mirrors, maps, etc.

FEATURES

- High density foam. hard than usual foam.
- Excellent holding power; peel strength and initial adhesion.
- Anti shock, heat and humidity resistance.
- Superior stick capabilities to different surfaces such as: metal; plastic; paper; wooden and silicon.

SMART TRADING ASIA (PVT) LTD

Lot No. 3, Maithree Mawatha, Industrial Estate, Ekala, Ja-Ela, Sri Lanka.
Tele: 011 4 324 280 | 011 4 324 281 | Hotline: 077 0 034 200-4 | Fax: 011 2 225 835
E-mail: smarttradingasia@gmail.com

Data Sheet

EVA foam Tape No.			EV3810H				
Thickness (mm)	0.5	0.8	1				
Adhesion to Steel (N/25mm)	22	17	14				
Holding Power (1kg/25mm/h)	24						
Color	Black						
Resist Temperature (Short time)	120℃						
Resist Temperature (Long time)	80℃						
Shelf life	24months						
Liner	PE Liner						

