SMART TRADING ASIA (PVT) LTD

Lot No. 3, IDB Industrial Estate, Maithree Mawatha, Ekala, Sri Lanka.
Tele: 011 4 324 280 | 011 4 324 281 | Hotline: 077 0 034 200-4 | Fax: 011 2 225 835
E-mail: smarttradingasia@gmail.com

PRODUCT DATA SHEET
CLOTH / DUCT TAPE

PRODUCT DESCRIPTION:

Cloth Duct Tape with aggressive adhesive and best-in-class performance for sealing, seaming, repairing, ducting, holding and waterproofing applications, as well as for tasks in the restoration industry. Duct tape offering excellent cold temperature performance; superior adhesion with quick stick; exceptional holding power for indoor and outdoor use; and easy tearability to finish jobs with speed and ease

FEATURES:

- High Tensile Strength.
- Instantly sticks to the surface
- High Sticky Power
- Excellent Cold Temperature Performance

TYPICAL PHYSICAL PROPERTIES:

Product Colour	**Black, Blue, Yellow, Red, Green**	**Silver**
Total Thickness	**160 Micron**	**160 Micron**
Mesh	**35**	**50**
Adhesive	Hot-Melt Base	Hot-Melt Base
180° Peel Adhesion (N25/MM)	≥16	≥17
Holding Power (hr)*	≥2	≥3
Tensile Strength (N25/MM)	85	108
Elongation (ASTM D 3759)*	12%	12%
Initial Tack (MM) 14#	≤60	≤60

Total Thickness Tolerance: ±10 micron

TYPICAL APPLICATIONS:

Heavy Duty Packaging, Bundling, General Applications, Gift Wrapping, Advertising, Marking, Suitable for Carpet Joints & Reinforced Protection for various Pipes & Objects, etc.

STORAGE & SHELF LIFE:

Product should be stored in a cool, dry area in original packing and to use within 12month of shipment & stored at 25°C (77°F) / 50% relative humidity out of direct sunlight.

SURFACE PREPARATION:

It is essential, as with all pressure-sensitive tapes that the surface to which the tape is applied must be clean, dry, and free of grease, oil or other contaminants.

PRODUCT USE:

It is essential that the user evaluate the Seal Master Tape product to determine whether it is fit for a particular purpose and user's method of application. Good results will be obtained when applied to a clean, dry surface with a suitable pressure on the Seal Master Tape product between +10 ~ +40°C (+50 ~ +105 °F).